





CM550S

Android Portable POS Printable Terminal









CM550S is integrated with NFC, Wi-Fi, GPS+BDS, thermal printer, PSAM Encryption protocol, and it also takes 1D/2D barcode scanner, UHF RFID, fingerprint identification and power infrared as optional modules. At the same time, CM550S supports the simultaneous configuration of both barcode scanning and UHF RFID scanning, which fully shows high-integration of handheld terminals.

Multi-industrial applications

Support for portable data collection in ticketing, clothing industry, logistics, meter reading, government & public affair, assets management, manufacturing, traceability, healthcare, retail, O2O payment areas and so on.







All in one

CM550S integrates barcode scanning, image collection, thermal printing, fingerprint recognition functions all in one, effectively meeting diversified operating needs of customers. It is the most reliable mobile handheld device for informationized enterprises.

Fingerprint identification

CM550S is able to meet different fingerprints demands of clients including normal fingerprint identification and USA FBI identification module.

Freely extended function of IoT

CILICO offers SDK redevelopment of fingerprinting. You can take advantage of any accessory applications on the Android platform to develop application programs. And you can get a real-time response from professional team of CILICO during developing.















With 5 inch HD LCD screen, the resolution is able to reach 1280*720. When operating, the clear screen brings the stunning visual experience to customers.

Large capacity lithium battery

Meanwhile, it is equipped with 4000mAh high quality battery, which ensures 8-hour continuous working. The double-row power supplier design is able to meet high demands of power when scanning and printing.

High speed Wi-Fi, smooth connection

Wi-Fi supports dual frequency seamless roaming with supreme communication performance. It could ensure the internet connection and quick data transmission under complicated working environment, such as warehouse and production line and so on.















CM550S Technical Parameters

Basic Param	eters							
Туре	Android Portab	le POS Printable Terr	minal					
CPU	Quad-core, ARM Cortex A7, 1.3GHz							
GPU	Mali-760-MP2							
Storage	2GB LPDDR3 RAM+16GB EMMC ROM							
os	Android 5.1							
Color	Black							
Screen	5'' high-resolution,1280*720 DPI,5 points-touch screen; Corning Gorilla Glass;							
Fingerprint sensor	r TCS1							
Printing	2" 384 thermal print head, print speed:20mm/s							
Communication	GSM:850/900/1800/1900,WCDMA:B1/B2/B5/B8, TDS-CDMA:B34/B39 LTE-TDD:B38/B39/B40,LTE-FDD:B1/B3/B7/B8/B20/B38/B39/B40							
GPS	Built-in GPS+BDS, support A-GPS, high accuracy position							
Interface	Micro USB2.0, support OTG							
Memory Interface	Micro SD Card, 2G~32G							
Bluetooth	Bluetooth 4.0, support BLE							
Audio	Built-in speaker, MIC, handset, 3.5mm headphone jack							
Wi-Fi	Support 802.11a/b/g/n mode, support 2.4GHz+5GHz seamless roaming							
Camera	8.0 Mega Pixel rear camera; 2.0 Mega Pixel front camera; Auto focus; with LED light							
Battery	Li-Polymer 4000mAh							
Standby	≧100h							
Duration	≧8h (full functio	on)						
IoTfunction	s (RFID, Ba	rcode)						
IOT barcode	mission and a second	le Scanner,2D barcode	Scanner					
1D Barcode	Code93, Code1	kland EAN, UCC Coup 1, Interleaved 2 of 5, I 1 DataBar, Composite	Discrete 2 of 5, Co	130	79	50	- TO	932,
2D Barcode	PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverse, Han Xin, Han Xin Inverse, etc.							
RFID		NFC, 14443A/B、1569 FID , EPC C1/G2, ISC			~5cm, read	ling position, batte	ery cover.	
WorkingEnv	ironment							
Operation Tempera	ature -25℃	~65°C (thermal print	er 0°C ~ 40°C)					
Storage Temperatu	ure -30°C~70°C							
Humidity	0~95	5% (non-condensing) (thermal printer	r 20% ~ 85°C)				
Product Fea	tures	200 0000	S 47 577					
3.8 0.41 ass	Support	Light Sensor	Support	Distance S	Sensor	Support	Handset	Suppoi
Gravity Sensor		Gyroscope	Support		person (1000) (10410) (107	e uniconstantal (IREO) (NEW AND CONTROL	100 CO
MIC Sensor	Support		12225		0	andard Cor	nfiguration	
MIC	(8.0)		Optional		3	ta li da la colo	THE STREET	
MIC	p e	100405000 33	Optional barcode scanner	0				luetooth 4
Ту	pe	100405000 33	barcode scanner	Qu	ıad-core, N	IFC, 4G dual card	ls dual standby, B	
Ту	(8.0)	• 1D Laser	barcode scanner de scanner	Wi	uad-core, N i-Fi 2.4G+5	IFC, 4G dual card 5G, GPS+BDS, 8.		
Ту	pe	1D Laser 2D barcoo	barcode scanner de scanner	Wi	uad-core, N i-Fi 2.4G+5	IFC, 4G dual card	ls dual standby, B	

CILICO Microelectronics Ltd.

XI'an HQ Address: 4F, Tower A, Hui Xin IBC, Zhang Ba 1st Rd, Hi-tech zone, Xi'an, Shaanxi province, China / Tel.: +86-29-88605865

Shenzhen Supply Chain Address: 3F, Tower 6B, Tai Hua Wu Tong Island, Xi Xiang Gu Shu Hang Kong Road, Bao'an District, Shenzhen,

Guangdong province, China / Tel.: +86-755-29120504